

L^AT_EX Class for The *Annals of Mathematics**

Boris Veytsman[†]

2017/05/09, v1.20

Abstract

This package provides a class for typesetting articles for The *Annals of Mathematics*

Contents

1	Introduction	3
2	User's Guide	3
2.1	Installation	3
2.2	Invocation	4
2.3	Top Matter	5
2.3.1	Commands for Authors	5
2.3.2	Commands for Editors	6
2.4	Additional Macros	8
2.5	Theorems	9
2.6	Illustrations	10
2.7	Bibliography	10
3	Implementation	12
3.1	Identification	12
3.2	Options	12
3.3	Loading Class and Packages	13
3.4	Internationalization	14
3.5	Fonts	14
3.6	Page Dimensions and Paragraphing	15
3.7	Headers	15
3.8	Top Matter Macros	17
3.9	Typesetting Top Matter	21
3.10	Typesetting End Matter	25
3.11	Sectioning	26

*©2010, Princeton University (Mathematics Department)

[†]borisv@lk.net, boris@varphi.com

3.12	Figures and Tables	27
3.13	Theorems	27
3.14	Bibliography Macros	28
3.15	Additional Macros	28
3.16	End of Class	29

1 Introduction

The *Annals of Mathematics* is published bimonthly with the cooperation of Princeton University and the Institute for Advanced Study. Founded in 1884 by Ormond Stone of the University of Virginia, the journal was transferred in 1899 to Harvard University, and in 1911 to Princeton University. Since 1933, the Annals has been edited jointly by Princeton University and the Institute for Advanced Study (see <http://annals.princeton.edu/annals/about/journal/about.html>).

This class presents a complete redesign of the journal style—with new fonts and new interface.

An author well acquainted with AMS \LaTeX should find this package easy to use and configurable. The User Manual below illustrates the basic use of the class and discusses the differences with `amsart`. For an in-depth tutorial of AMS \LaTeX I could recommend the excellent book [1].

2 User's Guide

2.1 Installation

The installation of the class follows the usual practice [2] for \LaTeX packages:

1. Run `latex` on `aomart.ins`. This will produce the file `aomart.cls`.
2. Put the file `aomart.cls` to the place where \LaTeX can find them (see [2] or the documentation for your \TeX system).
3. Update the database of file names. Again, see [2] or the documentation for your \TeX system for the system-specific details.
4. The file `aomart.pdf` provides the documentation for the package (this is the file you are probably reading now).

As an alternative to items 2 and 3 you can just put the files in the working directory where your `.tex` file is.

The class uses some other \LaTeX classes or packages. Most probably, they are already installed on your system. If not (or if their versions are very old), you need to download and install them. Here is the list:

1. `amsart` class and related packages [3],
2. Package `hyperref` [4],
3. `ifpdf` package [5],
4. `fancyhdr` package [6],
5. `cmtiup` package [7] for “special italics” with upright digits and punctuation. Note that since many distributions do not include this package, you may need to install it yourself. Just download the file <http://mirrors.ctan.org/fonts/cm/cmtiup.zip>, unzip it in your `TEXMF` directory and rebuild the file names database with the command like `mktexlsr`,

6. yhmath package [8].

2.2 Invocation

To use the class, put in the preamble of your document

```
\documentclass[options]{aomart}
```

The class internally loads `amsart`, so all facilities of `amsart` [1, 9] can be used in the source.

The class should work with the `Babel` [10] package. At present, English, French and German languages are fully supported.

options The options `draft` and `final` work in the same way as for `amsart` and standard
draft \LaTeX . If the option `draft` is chosen, the overfull lines are marked by black
final boxes on the margins *and* the `\includegraphics` prints blank placeholders for the
images. The option `final` (default) switches off the marking of overfull lines and
restores the behavior of `\includegraphics`. To switch on just the overfull marks,
without changing the behavior of `\includegraphics`, one can either explicitly
pass the option `final` to `graphics` package:

```
\documentclass[draft]{aomart}  
\usepackage[final]{graphics}
```

or add in the beginning of the document

```
\overfullrule=5pt
```

option The option `manuscript` is intended to facilitate the communications between
manuscript the editor and the author. It enables two things:

1. Numbering of lines in the manuscript is switched off in the normal mode, but is on in the manuscript mode.
2. Command `\EditorialComment` is no-op in normal mode, but produces marginal commentaries in the manuscript
3. Hyperlinks are black in normal mode, but blue in manuscript mode.

option The option `screen` is intended for the onscreen version of the article. If this
screen option is selected, the links are blue colored, and the margins are reduced.

option Starting from version 1.9 (2011) the formatting of DOI numbers changed ac-
olddoi cording to the new recommendations from CrossRef. The option `olddoi` switches
on the “old” formatting. It is used for compatibility reasons.

option Starting from version 1.5 (2016) the formatting of DOI numbers changed
doi2016 again according to Crossref recommendations. The option `doi2016` switches to
the version existed between 2011 and 2016.

option Since June 2017 keywords and AMS Mathematical Subjects classification num-
oldkeywords bers are printed on the title page. The option `oldkeywords` suppresses this.

options The size-changing options of `amsart` class (`8pt`, `9pt`, ..., `12pt`) have no effect other than producing a warning in the log since the journal is designed for only one type size (roughly corresponding to `11pt` of `amsart`).

`8pt`
`9pt`
`10pt`
`11pt`
`12pt`

2.3 Top Matter

There are two kinds of top matter commands: the ones used primarily for authors and the ones used primarily for editors. We describe them separately.

The macros described below must be issued in the preamble of the document, i.e. before `\begin{document}`. They produce fatal error otherwise. This behavior is required by the way non- \TeX scripts process the files to produce metadata.

The only exception is `abstract`, which should be placed between after `\begin{document}`.

2.3.1 Commands for Authors

`\title` The command `\title`, as in `amsart` class, has two arguments: one optional, and one mandatory:

`\title[ShortTitle]{FullTitle}`

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

The optional argument should be used in two cases: when the full title is too long to fit in the running head, *and* when the author wants to add a footnote or linebreaks to the title.

`\author` The interface for specifying the authors and their affiliations is close to the one of `amsart` [11] (and different from the standard \LaTeX). For each author a separate command `\author` should be used, followed by `\address` and (optionally) `\curraddr`, `\email`, `\urladdr` and `\orcid`. Note that the house style of the *Annals of Mathematics* requires writing `\address` in the form *Institution, City, State* (or *Institution, City, Country* for non-US locations). Like the newer versions of `amsart`, `aomart` does *not* require the doubling of the `@` symbols in the e-mail addresses. The macro `\author` has two arguments, similarly to `\title`:

`\author[AbbrevName]{FullName}`

The optional argument defines the shorter form of the author's name to be included in the running head.

`\givenname` The papers published in the *Annals of Mathematics* are included in various databases. For the indexing purposes it is important to correctly separate the authors' names into "First Name/Surname" parts. This operation is not easy for the computers. Therefore we decided that the authors should know best how to deal with their names. The macros `\givenname` and `\surname` are used to indicate how to split the name into the parts.

`\fulladdress` Another command which does not affect the typesetting is `\fulladdress`. It is used to store the full mailing address of the author for the online version of the journal and various databases.

`\shortauthors` In some cases the authors list may be too long for the running head, even if the abbreviated forms are used for each author. In this case it is possible to change the running head by a *redefinition* of the command `\shortauthors`. This redefinition must be done after all `\author` commands, but before `\maketitle`:

```
\renewcommand{\shortauthors}{A.~Smith et al}
```

`\thanks` Like `amsart` (and unlike standard L^AT_EX), `aomart` allows `\thanks` only *outside* of commands `\title` and `\author`.

`\copyrightnote` Normally each paper is copyrighted by Department of Mathematics, Princeton University. This is reflected in the footnote on the first page of the article. However, by arrangement with the editors, certain papers may have different copyright. The command `\copyrightnote{copyright statement}`, if issued, changes the footnote to the corresponding text, for example:

```
\copyrightnote{\textcopyright~2012 by the authors. This paper may  
be reproduced, in its entirety, for noncommercial purposes.}
```

Note that if you issue this command, you should explicitly include both the copyright sign and the year unless the paper does not have a copyright, for example:

```
\copyrightnote{This paper is in the public domain}
```

`abstract` The abstract of the paper must be put between `\begin{abstract}` and `\end{abstract}`. Unlike the situation in `amsart` class, `abstract` may be put *after* `\maketitle`.

`\maketitle` The macro `\maketitle` typesets the top matter. All top matter information should be specified before this command.

2.3.2 Commands for Editors

The commands described in this section should be used by the editors to insert the information about the published paper. They must be put before the `\maketitle` command.

`\keyword` The command `\keyword` adds a keyword to the list of keywords. This command may be repeated, for example

```
\keyword{Embedding theorem}  
\keyword{Relatively hyperbolic group}
```

`\subject` The command `\subject` has three parameters: whether the subject is primary or secondary, the classification scheme and the subject itself, for example

```
\subject{primary}{msc2000}{20E45}  
\subject{secondary}{msc2000}{20F65}
```

`\formatdate` The macro `\formatdate` is used to format the dates in the commands. Its argument is the date in the format `YYYY-MM-DD`, for example

```
\formatdate{2010-08-13}
```

`\received` The commands `\received`, `\revised`, `\accepted`, `\published`, `\publishedonline`
`\revised` accept as a parameter a date in the form `\formatdate{(YYYY-MM-DD)}`, for
`\accepted` example

```
\published \received{\formatdate{2004-12-24}}  
\publishedonline \revised{\formatdate{2006-04-12}}  
 \accepted{\formatdate{2007-10-02}}
```

`\proposed` The macros `\proposed`, `\seconded`, `\corresponding`, `\editor`, `\version` are
`\seconded` used to set the corresponding metadata for the editorial process, for example

```
\corresponding \proposed{E. D. Itor}  
 \editor \seconded{A. S. Sociate}  
 \version \corresponding{A. U. Thor}  
 \version{2.1}
```

`\volumenumber` The macros `\volumenumber`, `\issuenumber`, `\publicationyear`, `\papernumber`,
`\issuenumber` `\startpage`, `\endpage` set up the corresponding data for the paper, for example:

```
\publicationyear \volumenumber{172}  
 \papernumber \issuenumber{1}  
 \startpage \publicationyear{2010}  
 \endpage \papernumber{1}  
 \startpage{1}  
 \endpage{39}
```

Note that if the argument of `\endpage` is empty, \LaTeX tries to calculate the last page number as best as it can.

`\copyrightyear` In the standard copyright statement the copyright year is assumed to be the same as the `\publicationyear`. However, for special cases one can set the copyright year explicitly, for example,

```
\publicationyear{2012}  
\copyrightyear{2011}
```

Note that if you use your own copyright statement instead of the canned one (with the command `\copyrightnote`), you need to put there the copyright year explicitly instead of using this command.

`\doinumber` The macros `\doinumber`, `\mrnumber` and `\zblnumber` set the information
`\mrnumber` about paper in four major reference databases: DOI (<http://www.doi.org/>),
`\zblnumber` MathSciNet (<http://www.ams.org/mathscinet/>), Zentralblatt MATH (<http://www.zentralblatt-math.org/>),
`\arxivnumber` arXiv (<http://arxiv.org/>)

Code	Example
<code>\widetilde{AB}</code>	\widetilde{AB}
<code>\widehat{AB}</code>	\widehat{AB}
<code>\widetriangle{AB}</code>	\widetriangle{AB}
<code>\wideparen{AB}</code>	\wideparen{AB}
<code>\widering{AB}</code>	\widering{AB}
<code>\widebar{AB}</code>	\widebar{AB}

Table 1: Wide Mathematical Accents

[//www.zentralblatt-math.org/zmath/](http://www.zentralblatt-math.org/zmath/)) and arXiv (<https://www.arxiv.org>). The use of these macros should be obvious:

```
\doinumber{10.1215/S0012-7094-92-06520-3}
\mrnumber{1154181}
\zblnumber{0774.14039}
\arxivnumber{1234.567890}
```

Note the difference between these commands and the bibliography commands discussed in Section 2.7. Commands in this Section set up the data for the *current article*. Commands in Section 2.7 set up the data for the articles in the bibliography list.

Normally you should *not* use `\doinumber` command, since the class will construct the standard DOI for the paper from the volume, issue and paper information. Use it *only* if the result is by any reason wrong.

`\oldsubsections` Starting with version 1.2 we decreased the vertical spacing before `\subsection`. The command `\oldsubsections` restores the “old” values.

2.4 Additional Macros

`eqnarray` Thee class aomart loads the class amsart. Therefore all familiar amsmath commands [9] are available. In particular, there are many commands for writing multiline equations (`split`, `align`, `gather`, `multline`, ...). The environments `eqnarray` and `eqnarray*`, while still available, are *not* recommended and should be avoided if possible.

`\widetilde` A number of “wide” mathematical accents is available due to the (internally loaded) package yhmath [8]: `\widetilde`, `\widehat`, `\widetriangle`, `\wideparen`, `\widering`, `\widebar`. See Table 1 for the example of the usage.

`\wideparen` The macro `\EditorialComment[⟨comments⟩]` typesets the comments on the margins in the `manuscript` mode, for example,

```
\widering
\widebar
\EditorialComment Erd\os proved the following theorem.\EditorialComment{A citation is needed}
```


`\fullref` A set of macros is used to make more convenient clickable references in the on-line versions of papers. The package `hyperref` [4] makes clickable reference numbers in the phrases like

`\pfullref`
`\bfullref`
`\eqfullref`

```
...in theorem~\ref{thm:Noeter}...
...see equation~\eqref{eq:alpha}...
```

However, it is more convenient for the readers if both the number *and* the word “theorem” or “equation” were clickable. The macros `*fullref` solve this problem. Each macro has two arguments: the word and the reference, for example

```
...in \fullref{theorem}{thm:Noeter}...
```

The command `\pfullref` typesets the reference in parentheses. The command `\bfullref` typesets it in brackets, and the command `\eqfullref` uses the `\eqref` command, for example,

```
...see \eqfullref{equation}{eq:alpha}...
```

The Perl script `fullref.pl` can be used to convert change all references to the `\fullref` commands. It works in the following way:

```
perl fullref.pl original.pl > result.pl
```

The script converts all instances of combinations “word `\ref{reference}`” and “word~`\ref{reference}`” to “`\fullref{word}{reference}`”, and similarly for parenthesized references or `\eqref` commands. To prevent the converting, just put `\ref{reference}` or `\eqref{reference}` inside braces. The “word” here must not start with a backslash (i.e. must not be a macro itself). This prevents disastrous results for phrases like “see~`\ref{a}`, `\ref{b}`”.

The distribution includes two sample files, `aomsample.tex` and `aomsample1.tex`, the latter being obtained from the former by the script `fullref.pl`.

Note that `\autoref` command of `hyperref` provides for another mechanism that achieves the same goal. Unlike `\fullref` command, the command `\autoref` tries to figure out the name of the reference from the context. See the manual [4] for more information.

2.5 Theorems

`\newtheorem` You can use the commands of `amsthm` package [12] like `\newtheorem{lem}{Lemma}` for numbered theorems, or `\newtheorem*{KL}{Klein’s Lemma}` for unnumbered theorems, or tune the numbering using the optional arguments of these commands.

To provide backward compatibility with some other classes used internally by the *Annals of Mathematics*, the class provides yet another optional argument for the command `\newtheorem`, allowing constructions like `\newtheorem[it]{lem}{Lemma}`. This optional parameter is not used in our typesetting.

The class provides two theorem styles:

plain: This is the default theorem style. It is used for Theorem, Lemma, Proposition, Conjecture, Corollary and Claim.

definition: This style is used for Definition, Remark, Notation, Condition, Example etc.

Note that AMS classes define the third theorem style, **remark**. In our class remarks are typeset in the **definition** style. To make the authors' lives easier we define the theorem style **remark**, which is identical to the theorem style **definition**.

2.6 Illustrations

The authors can use the `graphics`, `graphicx`, `PSTricks`, `pgf/tikz`, `Metapost` or other tools to include illustrations (see [13] for a comprehensive discussion of L^AT_EX graphics possibilities).

2.7 Bibliography

The authors are encouraged to use BibT_EX for uniform style of bibliography. The distribution includes the BST files `aomplain.bst` and `aomalpha.bst`. These files have several additional non-standard fields:

mrnumber: MathSciNet number for the article.

zblnumber: Zentralblatt number for the article.

doi: DOI number for the article.

jfmnumber: JFM number for the article.

arxiv: ArXiv reference for the ArXiv manuscript.

url: If the reference is available online, the corresponding url.

venue: (for `conference` entries) The place where the conference took place.

sortyear: Some entries do not have a year set up (e.g. some `unpublished` entries). If you have several entries from the same author, some with a year, and some without, you may want to put them in a certain order. The field `sortyear` overrides `year` for the sorting purposes.

titlenote: this field is like `note`, but is typeset immediately after a title. It should be used for additional information, for example,

```
@Book{Knuth94:TheTeXbook,
  author = {Knuth, Donald Ervin},
  title = {The \TeX book},
  publisher = {Addison-Wesley Publishing Company},
  year = 1994,
```

```
series = {Computers \& Typesetting A},
address = {Reading, MA},
titlenote = {with illustrations by Duane Bibby}
}
```

totalpages: some articles (especially published in an electronic format) do not have start and end page numbers; instead you may put the total number of pages. If both **pages** and **totalpages** are present, **pages** take precedence.

`\doi` There are several databases routinely used in the science and mathematics communities. Among them are DOI, MathSciNet, Zentralblatt, Jahrbuch Database, `\mr` ArXiv. Many bibliographies include references to these databases. The commands `\zbl` `\doi`, `\mr`, `\zbl`, `\jfm`, `\arxiv` are used to typeset these references. If you use `\jfm` Bib_TE_X, these commands are automatically used for the corresponding fields in `\arxiv` your database entries.

3 Implementation

3.1 Identification

We start with the declaration who we are. Most `.dtx` files put driver code in a separate driver file `.drv`. We roll this code into the main file, and use the pseudo-guard `<gobble>` for it.

```
1 <class>\NeedsTeXFormat{LaTeX2e}
2 <*gobble>
3 \ProvidesFile{aomart.dtx}
4 </gobble>
5 <class>\ProvidesClass{aomart}
6 [2017/05/09 v1.20 Typesetting articles for the Annals of Mathematics]
```

And the driver code:

```
7 <*gobble>
8 \documentclass{ltxdoc}
9 \usepackage{array,booktabs,amsmath,graphics}
10 \let\widebar\overline
11 \usepackage{url}
12 \usepackage{amsfonts,yhmath}
13 \usepackage[breaklinks,colorlinks,linkcolor=black,citecolor=black,
14             pagecolor=black,urlcolor=black,hyperindex=false]{hyperref}
15 \PageIndex
16 \CodelineIndex
17 \RecordChanges
18 \EnableCrossrefs
19 \begin{document}
20   \DocInput{aomart.dtx}
21 \end{document}
22 </gobble>
23 <*class>
```

3.2 Options

The size-changing options produce a warning:

```
24 \long\def\aom@size@warning#1{%
25   \ClassWarning{aomart}{Size-changing option #1 will not be
26     honored}}%
27 \DeclareOption{8pt}{\aom@size@warning{\CurrentOption}}%
28 \DeclareOption{9pt}{\aom@size@warning{\CurrentOption}}%
29 \DeclareOption{10pt}{\aom@size@warning{\CurrentOption}}%
30 \DeclareOption{11pt}{\aom@size@warning{\CurrentOption}}%
31 \DeclareOption{12pt}{\aom@size@warning{\CurrentOption}}%
```

```
\if@aom@manuscript@mode Check whether we are in the manuscript mode
```

```
32 \newif\if@aom@manuscript@mode
33 \@aom@manuscript@modefalse
34 \DeclareOption{manuscript}{\@aom@manuscript@modetrue}
```

```

\if@aom@screen@mode Check whether we are in the screen mode
35 \newif\if@aom@screen@mode
36 \@aom@screen@modefalse
37 \DeclareOption{screen}{\@aom@screen@modetrue}

\if@aom@olddoi DOI processing is different in the “old” and new mode.
38 \newif\if@aom@olddoi
39 \@aom@olddoifalse
40 \DeclareOption{olddoi}{\@aom@olddoittrue}

\if@aom@doiMMXVI DOI processing is different in the 2016 and new mode
41 \newif\if@aom@doiMMXVI
42 \@aom@doiMMXVIfalse
43 \DeclareOption{doi2016}{\@aom@doiMMXVItrue}

\if@aom@oldkeywords Keywords processing is different in the “old” and new mode.
44 \newif\if@aom@oldkeywords
45 \@aom@oldkeywordsfalse
46 \DeclareOption{oldkeywords}{\@aom@oldkeywordstrue}

All other options are passed to amsart:
47 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{amsart}}

Now we read the configuration file
48 \InputIfFileExists{aomart.cfg}{%
49 \ClassInfo{aomart}{%
50 Loading configuration file aomart.cfg}}{%
51 \ClassInfo{aomart}{%
52 Configuration file aomart.cfg is not found}}

And process the options:
53 \ProcessOptions\relax

```

3.3 Loading Class and Packages

We start with the base class

```

54 \LoadClass[11pt]{amsart}

A bunch of packages:
55 \RequirePackage{fancyhdr, lastpage, ifpdf}
56 \RequirePackage[breaklinks,colorlinks]{hyperref}
57 \if@aom@screen@mode
58 \hypersetup{linkcolor=blue,citecolor=blue,
59 urlcolor=blue, pdfpagescrop={110 705 500 80}}%
60 \else\if@aom@manuscript@mode
61 \hypersetup{linkcolor=blue,citecolor=blue,
62 urlcolor=blue}%
63 \else
64 \hypersetup{linkcolor=black,citecolor=black,
65 urlcolor=black}%

```

```
66 \fi\fi
67 \urlstyle{rm}
```

Amsart has `\collect@body` macro. However, we want the `\long` version, so we use `environ`

```
68 \RequirePackage{environ}
```

3.4 Internationalization

There are some papers published in languages other than English. The Babel is expected to be used for them. Here we add some macros extending captions for these languages.

First, let us define English defaults:

```
\@aom@by This is just "By" in English:
69 \def\@aom@by{By}
```

```
\@aom@and This is "and" in English:
70 \def\@aom@and{and}
```

Now we can define internationalization:

```
71 \AtBeginDocument{\@ifpackageloaded{babel}{%
72 \addto\captionsfrench{\def\@aom@by{Par}\def\@aom@and{et}}%
73 \addto\captionsgerman{\def\@aom@by{Von}\def\@aom@and{und}}%
74 \addto\captionsenglish{\def\@aom@by{By}\def\@aom@and{and}}{}}
```

3.5 Fonts

We use `yhmath` for wide symbols:

```
75 \RequirePackage{yhmath}
```

We need `cmtiup` package, but we may find out it is not installed.

```
76 \IfFileExists{cmtiup.sty}{%
77 \RequirePackage{cmtiup}}{%
78 \ClassWarning{aomart}{The package mdputu is not found.\MessageBreak
79 You need this package to get italics with upright digits!}}
```

`\specialdigits` A legacy macro. We do not need it anymore.

```
80 \def\specialdigits{}%
81 \let\sishape=\itshape
82 \let\textsi=\textit
```

The `amsart` class defines several options for different font sizes (10pt, 11pt, etc). We have just one design size for the articles.

`\@typesizes` The font information in `amsart` is stored in `\@typesizes` macro. It has 11 type-sizes: 5 below and 5 above `\normalsize` .

```
83 \def\@typesizes{%
84 \or{\@vopt}{9}\or{\@viipt}{9}\or{\@viipt}{9}\or{\@ixpt}{12}%
```

```

85 \or{\@xpt}{13}%
86 \or{\@xipt}{14}% normalsize
87 \or{\@xiipt}{15}\or{13}{17}\or{\@xviipt}{20}%
88 \or{19}{23.2}\or{22}{27.8}}%
89 \normalsize \linespacing=\baselineskip

```

`\widebar` The functionality of `\widebar` coincides with that of `amsmath \overline`:

```

90 \let\widebar\overline

```

3.6 Page Dimensions and Paragraphing

`\textwidth` These are from the old `aomamlt2e`:

```

\textheight 91 \setlength{\textwidth}{31pc}
92 \setlength{\textheight}{48pc}

```

`\evensidemargin` The margins:

```

\oddsidemargin 93 \oddsidemargin=.65in
94 \evensidemargin=.65in

```

`\footins` Some skips from `aomamlt2e`:

```

\topskip 95 \setlength{\topskip}{12pt}
\abovedisplayskip 96 \setlength{\abovedisplayskip}{6.95pt plus3.5pt minus 3pt}
\belowdisplayskip 97 \setlength{\belowdisplayskip}{6.95pt plus4.5pt minus 3pt}
98 \setlength{\skip\footins}{20pt}
99 \setlength{\dimen\footins}{3in}

```

`\footskip` Some space for footnotes:

```

100 \setlength\footskip{30pt}

```

`\parskip` Paragraph shape:

```

\parindent 101 \setlength{\parindent}{22pt}
102 \setlength{\parskip}{\z@}

```

`\widowpenalty` We suppress widows and clubs:

```

\clubpenalty 103 \widowpenalty=10000
104 \clubpenalty=10000

```

3.7 Headers

`\headsep` Separation between the header and the body

```

105 \setlength{\headsep}{14pt}

```

`\headrulewidth` We do not want decorative rules in the journal:

```

\footrulewidth 106 \renewcommand{\headrulewidth}{0pt}
107 \renewcommand{\footrulewidth}{0pt}

```

`\@aom@linecount` This is the box displayed in the manuscript mode

```
108 \if@aom@manuscript@mode
109 \newsavebox{\@aom@linecount}
110 \savebox{\@aom@linecount}[4em][t]{\parbox[t]{4em}{%
111 \@tempcnta\@ne\relax
112 \loop{\underline{\scriptsize\the\@tempcnta}}\@ne\@tempcnta}}\@ne\@tempcnta}}
113 \advance\@tempcnta by \@ne\ifnum\@tempcnta<43\repeat}}
114 \fi
```

It is easy to set up headers with fancyhdr:

```
115 \pagestyle{fancy}
116 \fancyhead{}
117 \fancyfoot{}
118 \fancyhead[CO]{\scriptsize\shorttitle}
119 \fancyhead[RO,LE]{\footnotesize\thepage}
120 \if@aom@manuscript@mode
121 \fancyhead[LE]{\footnotesize\thepage\begin{picture}(0,0)%
122 \put(-26,-25){\usebox{\@aom@linecount}}}%
123 \end{picture}}
124 \fancyhead[L0]{\begin{picture}(0,0)%
125 \put(-21,-25){\usebox{\@aom@linecount}}}%
126 \end{picture}}
127 \fancyfoot[C]{\scriptsize Proof: page numbers may be temporary}
128 \fi
129 \fancyhead[CE]{\scriptsize\MakeUppercase\shortauthors}
```

The first page has the special headers. The style `firstpage` is invoked by `amsart`; here we just redefine it.

```
130 \fancypagestyle{firstpage}{%
131 \fancyhf{}%
132 \if@aom@manuscript@mode
133 \lhead{\begin{picture}(0,0)%
134 \put(-21,-25){\usebox{\@aom@linecount}}}%
135 \end{picture}}
136 \fi
137 \chead{\scriptsize%
138 \href{\@annalsurl}{Annals of Mathematics} \textbf{\currentvolume}
139 (\currentyear),
```

We always print the starting page. However, we print the last page only if it does not coincide with the first page. There are two cases here: first, the last page may still be `\pageref{LastPage}`. In this case we need to extract the numerical value of the counter—note that `hyperref` is in action! Second, we could redefine the last page, and it is no longer `\pageref{LastPage}`. In this case we need to compare the value with the first page.

```
140 \start@page%
141 \def\tempa{\pageref{LastPage}}%
142 \edef\tempb{\start@page}%
143 \ifx\tempa\end@page
144 \edef\tempa{\HyPsd@@@pageref{LastPage}}%
```



```

145 \else
146 \edef\tempa{\end@page}%
147 \fi
148 \ifx\tempa\tempb\else--\end@page\fi\
149 \ifx@doinumber\empty\else
150 \edef@doinumber{\@doinumber}%
151 \expandafter\doi\expandafter{\@doinumber}\fi}%
152 \cfoot{\footnotesize\thepage}}%

```

```

\annalsurl The command to set up the URL of the journal
153 \def\annalsurl#1{\gdef\annalsurl{#1}}
154 \annalsurl{http://annals.math.princeton.edu/about}

```

3.8 Top Matter Macros

We make these macros allowed only in the preamble:

```

155 \@onlypreamble{\title}
156 \@onlypreamble{\author}
157 \@onlypreamble{\email}
158 \@onlypreamble{\address}
159 \@onlypreamble{\curraddr}
160 \@onlypreamble{\urladdr}
161 \@onlypreamble{\orcid}
162 \@onlypreamble{\givenname}
163 \@onlypreamble{\fulladdress}
164 \@onlypreamble{\surname}
165 \@onlypreamble{\thanks}
166 \@onlypreamble{\keyword}
167 \@onlypreamble{\subject}
168 \@onlypreamble{\received}
169 \@onlypreamble{\revised}
170 \@onlypreamble{\accepted}
171 \@onlypreamble{\published}
172 \@onlypreamble{\publishedonline}
173 \@onlypreamble{\proposed}
174 \@onlypreamble{\seconded}
175 \@onlypreamble{\corresponding}
176 \@onlypreamble{\editor}
177 \@onlypreamble{\version}
178 \@onlypreamble{\volumenumber}
179 \@onlypreamble{\issuenumber}
180 \@onlypreamble{\publicationyear}
181 \@onlypreamble{\copyrightnote}
182 \@onlypreamble{\copyrightyear}
183 \@onlypreamble{\papernumber}
184 \@onlypreamble{\startpage}
185 \@onlypreamble{\endpage}
186 \@onlypreamble{\doinumber}
187 \@onlypreamble{\mrnumber}

```

```
188 \@onlypreamble{\zblnumber}
189 \@onlypreamble{\arxivnumber}
```

Most top matter macros are defined in amsart. Here we just add some new macros and redefine some.

`\fulladdress` We store the information to output it later in the rpi file

```
\givenname 190 \def\@names{}
\surname 191 \def\givenname#1{\g@addto@macro\@names{givenname=#1;}}
192 \def\surname#1{\g@addto@macro\@names{surname=#1;}}
193 \def\fulladdress#1{\g@addto@macro\@names{fulladdress=#1;}}
```

`\author` We add mangling of `\@names` to the amsart macro

```
194 \renewcommand{\author}[2] [] {%
195   \ifx\@empty\authors
196     \gdef\authors{#2}%
197     \g@addto@macro\@names{author=#2;}%
198   \else
199     \g@addto@macro\authors{\and#2}%
200     \g@addto@macro\@names{\and author=#2;}%
201     \g@addto@macro\addresses{\author{}}%
202   \fi
203   \@ifnotempty{#1}{%
204     \ifx\@empty\shortauthors
205       \gdef\shortauthors{#1}%
206     \else
207       \g@addto@macro\shortauthors{\and#1}%
208     \fi
209   }%
210 }
211 \edef\author{\@nx\@dblarg
212   \@xp\@nx\csname\string\author\endcsname}
```

`\email` We change amsart macro to output metadata

```
213 \renewcommand{\email}[2] [] {%
214   \g@addto@macro\addresses{\email{#1}{#2}}%
215   \g@addto@macro\@names{email=#2;}%
216 }
```

`\urladdr` We change amsart macro to output metadata

```
217 \renewcommand{\urladdr}[2] [] {%
218   \g@addto@macro\addresses{\urladdr{#1}{#2}}%
219   \g@addto@macro\@names{urladdr=#2;}%
220 }
```

`\orcid` Orcid also outputs metadata

```
221 \newcommand{\orcid}[2] [] {%
222   \g@addto@macro\addresses{\orcid{#1}{#2}}%
223   \g@addto@macro\@names{orcid=#2;}%
224 }
```

`\keyword` Actually `amsart` has `\keywords` macro. It redefines `\@keywords`. Our macro adds to the stack instead.

```

225 \def\keyword#1{\ifx\@keywords\@empty\gdef\@keywords{#1}\else
226 \g@addto@macro\@keywords{, #1}\fi}

```

`\subject` Subjects:

```

227 \let\@primarysubjects\@empty
228 \let\@secondarysubjects\@empty
229 \def\subject#1#2#3{%
230 \expandafter\ifx\csname @#1subjects\endcsname\@empty\relax
231 \expandafter\gdef\csname @#1subjects\endcsname{#3}%
232 \else
233 \expandafter\g@addto@macro\csname @#1subjects\endcsname{, #3}%
234 \fi}

```

`\formatdate` This just sends the date to the special macro `\@formatdate`

```

235 \def\formatdate#1{\@formatdate#1\@endformatdate}

```

`\@formatdate` This macro takes date in the form YYYY-MM-DD and properly formats it. Note how we delete the leading zero in dates like April 02.

```

236 \def\@formatdate#1-#2-#3\@endformatdate{%
237 \@tempcnta=#3\relax
238 \ifcase#2\or
239 January\or February\or March\or April\or May\or June\or
240 July\or August\or September\or October\or November\or December\fi
241 \space\the\@tempcnta,\space#1}

```

`\received` The following macros add stuff to the footnotes material:

```

\revised 242 \def\received#1{\def\@received{#1}}
\accepted 243 \let\@received\@empty
\published 244 \def\revised#1{\def\@revised{#1}}
\publishedonline 245 \let\@revised\@empty
246 \def\accepted#1{\def\@accepted{#1}}
247 \let\@accepted\@empty
248 \def\published#1{\def\@published{#1}}
249 \let\@published\@empty
250 \def\publishedonline#1{\def\@publishedonline{#1}}
251 \let\@publishedonline\@empty

```

The next macros mimic the functionality of `amsart \issueinfo` command. Note that `\issueinfo` still works.

`\volumenumber` This sets the volume of the paper

```

252 \def\volumenumber#1{\def\currentvolume{#1}}

```

`\issuenumber` This sets the issue of the paper:

```

253 \def\issuenumber#1{\def\currentissue{#1}}

```

`\publicationyear` This sets the year of the paper
254 `\def\publicationyear#1{\def\currentyear{#1}}`

`\papernumber` This is absent from the `\issueinfo`.
255 `\def\papernumber#1{\def\currentpaper{#1}}`
256 `\papernumber{0000}`

`\startpage` This defines the starting page of the paper. We have some nice features to set up roman page numbers for editorial stuff—probably not needed for this journal at this time. . .
257 `\def\startpage#1{\pagenumbering{arabic}\setcounter{page}{#1}%`
258 `\def\start@page{#1}%`
259 `\ifnum\c@page<\z@ \pagenumbering{roman}\setcounter{page}{-#1}%`
260 `\def\start@page{\romannumeral#1}%`
261 `\fi}`

`\endpage` This macro again has a twist in it: if the argument is not set, it calculates the last page number itself.
262 `\def\endpage#1{\def@tempa{#1}%`
263 `\ifx@tempa@empty\def\end@page{\pageref{LastPage}}%`
264 `\else\def\end@page{#1}\fi}`

`\pagespan` This macro is different from the one provided by `amsart` because we want to have the option of automatic calculation of the last page number.
265 `\def\pagespan#1#2{\startpage{#1}\endpage{#2}}`
266 `\pagespan{1}{}`

`\@getabstract` `Amsart` typesets the abstract in a box. We preserve this peculiarity, but we need to put abstract in a macro to output in the `rpi` file.
267 `\long\def@aom@abstract{}`
268 `\long\def\@getabstract#1{%`
269 `\long\gdef@aom@abstract{#1}%`
270 `\ifx\maketitle\relax`
271 `\ClassWarning{aomart}{Abstract should precede`
272 `\protect\maketitle\space in AMS derived classes}%`
273 `\fi`
274 `\global\setbox\abstractbox=\vtop\bgroup%`
275 `\vglue1pc%`
276 `{\centering\normalfont\normalsize\bfseries\abstractname\par\vglue1pc}%`
277 `\list-{}{\labelwidth\z@%`
278 `\leftmargin3pc \rightmargin\leftmargin%`
279 `\listparindent\normalparindent \itemindent\normalparindent%`
280 `\parsep\z@ \@plus\p@%`
281 `\let\fullwidthdisplay\relax%`
282 `}%`
283 `\item[]\normalfont\Small#1`
284 `\endlist\egroup}`

`abstract` This puts abstract in a box *and* in a macro. Wasteful, but backward compatible
285 `\renewenvironment{abstract}{\Collect@Body\@getabstract}{%`
286 `\ifx\@setabstract\relax\@setabstracta\fi}`

`\proposed` We do not typeset the name of the proposer
287 `\let\proposed\@gobble`

`\seconded` Or the seconder
288 `\let\seconded\@gobble`

`\corresponding` This is the corresponding author—again not typeset
289 `\let\corresponding\@gobble`

`\version` We do not typeset the current version of the manuscript either...
290 `\let\version\@gobble`

`\doinumber` Now databases' numbers of the article:
`\mrnumber` 291 `\def\doinumber#1{\gdef\@doinumber{#1}}`
`\zblnumber` 292 `\doinumber{10.4007/annals.\currentyear.\currentvolume.\currentissue.\currentpaper}`
`\arxivnumber` 293 `\def\mrnumber#1{\gdef\@mrnumber{#1}}`
294 `\mrnumber{}`
295 `\def\zblnumber#1{\gdef\@zblnumber{#1}}`
296 `\zblnumber{}`
297 `\def\arxivnumber#1{\gdef\@arxivnumber{#1}}`
298 `\arxivnumber{}`

`\copyrightyear` This is the copyright year in case it does not coincide with the publication year:
299 `\def\copyrightyear#1{\def\@copyrightyear{#1}}`
300 `\copyrightyear{}`

`\copyrightnote` This is the copyrightnote. The default has some trickery with the year:
301 `\def\copyrightnote#1{\def\@copyrightnote{#1}}`
302 `\copyrightnote{\textcopyright~%`
303 `\ifx\@empty\@copyrightyear\currentyear\else\@copyrightyear\fi~%`
304 `Department of Mathematics, Princeton University}`

3.9 Typesetting Top Matter

`\@mainrpi` We write the information about the paper into file.rpi (the The stream for the rpi file:
305 `\newwrite\@mainrpi`

`\aom@write@paper@info` This writes the information about the paper into the file jobname.rpi. Note that hyperref makes our life a little bit more complex
306 `\def\aom@write@paper@info{%`
307 `\bgroup`
308 `\if@filesw`
309 `\openout\@mainrpi\jobname.rpi%`

```

310 \def\and{\string\and\space}%
311 \ifx\r@LastPage\undefined
312 \edef\@tempa{\start@page}%
313 \else
314 \def\@tempc##1##2##3##4##5{##2}%
315 \edef\@tempa{\expandafter\@tempc\r@LastPage}%
316 \fi
317 \protected@write\@mainrpi{}%
318 {\@percentchar authors=\authors}%
319 \protected@write\@mainrpi{}%
320 {\@percentchar authors.information={\@names}}%
321 \protected@write\@mainrpi{}%
322 {\@percentchar title=\@title}%
323 \protected@write\@mainrpi{}%
324 {\@percentchar year=\currentyear}%
325 \protected@write\@mainrpi{}%
326 {\@percentchar volume=\currentvolume}%
327 \protected@write\@mainrpi{}%
328 {\@percentchar issue=\currentissue}%
329 \protected@write\@mainrpi{}%
330 {\@percentchar paper=\currentpaper}%
331 \protected@write\@mainrpi{}%
332 {\@percentchar startpage=\start@page}%
333 \protected@write\@mainrpi{}%
334 {\@percentchar endpage=\@tempa}%
335 \protected@write\@mainrpi{}%
336 {\@percentchar doi=\@doinumber}%
337 \ifx\@zblnumber\@empty\else
338 \protected@write\@mainrpi{}%
339 {\@percentchar zbl=\@zblnumber}%
340 \fi
341 \ifx\@mrnumber\@empty\else
342 \protected@write\@mainrpi{}%
343 {\@percentchar mr=\@mrnumber}%
344 \fi
345 \ifx\@arxivnumber\@empty\else
346 \protected@write\@mainrpi{}%
347 {\@percentchar arxiv=\@arxivnumber}%
348 \fi
349 \protected@write\@mainrpi{}%
350 {\@percentchar subjects=Primary \@primarysubjects; Secondary:
351 \@secondarysubjects}%
352 \protected@write\@mainrpi{}%
353 {\@percentchar keywords=\@keywords}%
354 \protected@write\@mainrpi{}%
355 {\@percentchar abstract=\@aom@abstract}%
356 \closeout\@mainrpi
357 \fi
358 \egroup}

```

```

\@maketitle@hook We add writing the information to the hook:
359 \def\@maketitle@hook{\aom@write@paper@info\global\let\@maketitle@hook\empty}

\@settitle We do not uppercase title. Also, we use this occasion to set PDF information:
360 \def\@settitle{\begin{center}%
361 \baselineskip20\p@\relax
362 \bfseries\LARGE
363 \@title
364 \ifpdf
365 \hypersetup{pdftitle=\@title}%
366 \fi
367 \end{center}%
368 }

\@setauthors Now we typeset authors according to our specs. Again, we use this occasion to
set some PDF information:
369 \def\@setauthors{%
370 \ifx\authors\empty\relax\else
371 \begingroup
372 \def\thanks{\protect\thanks@warning}%
373 \trivlist
374 \centering\footnotesize \@topsep30\p@\relax
375 \advance\@topsep by -\baselineskip
376 \item\relax
377 \def\@and{{\upshape \@aom@and}}
378 \author@andify\authors
379 \ifpdf
380 \hypersetup{pdfauthor=\authors}%
381 \fi
382 \def\{\protect\linebreak}%
383 \small \@aom@by{} \scshape\authors%
384 \ifx\empty\contribs
385 \else
386 ,\penalty-3 \space \@setcontribs
387 \clocsetocontribs
388 \fi
389 \endtrivlist
390 \endgroup
391 \fi}

\@setcontribs Contributors are set up in the same way as authors:
392 \def\@setcontribs{%
393 \xcontribs
394 {\scshape \xcontribs}%
395 }

\@adminfootnotes We do not typeset keywords, so we change the definition:
396 \def\@adminfootnotes{%
397 \let\@makefnmark\relax \let\@thefnmark\relax

```

```

398 \ifx\@empty\@date\else \@footnotetext{\@setdate}\fi
399 \ifx\@empty\@subjclass\else \@footnotetext{\@setsubjclass}\fi
400 \ifx\@empty\@keywords\else\@setkeywords\fi
401 \ifx\@empty\@primarysubjects
402     \ifx\@empty\@secondarysubjects
403     \else\@setsubjects\fi
404 \else\@setsubjects\fi
405 \ifx\@empty\thankses\else \@footnotetext{%
406     \def\par{\let\par\@par}\@setthanks}%
407 \fi
408 \ifx\@empty\@copyrightnote\else \@footnotetext{%
409     \def\par{\let\par\@par}\@copyrightnote\@addpunct.}%
410 \fi
411 }

```

`\@setkeywords` Typesetting keywords

```

412 \def\@setkeywords{%
413     \ifpdf
414     \hypersetup{pdfkeywords=\@keywords}%
415     \fi
416     \if@aom@oldkeywords\else
417     \@footnotetext{Keywords: \@keywords}%
418     \fi
419 }

```

`\@setsubjects` Setting subjects

```

420 \def\@setsubjects{%
421     \let\@subjects\@empty
422     \ifx\@primarysubjects\@empty\else
423     \edef\@subjects{Primary: \@primarysubjects}%
424     \fi
425     \ifx\@secondarysubjects\@empty\else
426     \ifx\@primarysubjects\@empty
427     \edef\@subjects{Secondary: \@secondarysubjects}%
428     \else
429     \edef\@subjects{\@subjects; Secondary: \@secondarysubjects}%
430     \fi
431     \fi
432     \ifpdf
433     \hypersetup{pdfsubject=\@subjects}%
434     \fi
435     \if@aom@oldkeywords\else
436     \@footnotetext{AMS Classification: \@subjects.}%
437     \fi
438 }

```

`\@@and` We want “and” in the footers to be lowercase. Since there is some uppercase involved, we protect it:

```

439 \def\@@and{\MakeLowercase{\@aom@and}}

```


3.10 Typesetting End Matter

End matter is typeset at the end of the paper.

```
\enddoc@text This is the main macro for typesetting endmatter.
440 \def\enddoc@text{%
441   \ifx\@empty\@translators \else\@settranslators\fi
442   \ifx\@empty\@received \else\@setreceived\fi
443   \ifx\@empty\@revised \else\@setrevised\fi
444   \ifx\@empty\addresses \else\@setaddresses\fi

\@setreceived A bunch of macros for setting centered dates
\@setrevised 445 \def\@setreceived{\centering(Received: \@received)\par}}
\@setaccepted 446 \def\@setrevised{\centering(Revised: \@revised)\par}}
\@setpublished 447 \def\@setaccepted{\centering(Accepted: \@accepted)\par}}
\@setpublishedonline 448 \def\@setpublished{\centering(Published: \@published)\par}}
449 \def\@setpublishedonline{\centering(Published online: \@publishedonline)\par}}

\emailaddrname We do not want the word “address” here:
450 \def\emailaddrname{\itshape E-mail}}

\@setaddresses The difference between our definition and the one in amsart is that we want the
e-mail and URL to be clickable
451 \def\@setaddresses{\par
452   \nobreak \begingroup
453   \footnotesize
454   \def\author##1{\nobreak\addvspace\bigskipamount}%
455   \def\{\unskip, \ignorespaces}%
456   \interlinepenalty\@M
457   \def\address##1##2{\begingroup
458     \par\addvspace\bigskipamount\indent
459     \@ifnotempty{##1}{\ignorespaces##1\unskip} }%
460     {\scshape\ignorespaces##2}\par\endgroup}%
461   \def\curraddr##1##2{\begingroup
462     \@ifnotempty{##2}{\nobreak\indent\curraddrname
463       \@ifnotempty{##1}{, \ignorespaces\scshape##1\unskip}\hskip0.2em:\space
464       \scshape##2\par}\endgroup}%
465   \def\email##1##2{\begingroup
466     \@ifnotempty{##2}{\nobreak\indent\emailaddrname
467       \@ifnotempty{##1}{, \ignorespaces##1\unskip}\hskip0.2em:\space
468       \href{mailto:##2}{\nolinkurl{##2}}\par}\endgroup}%
469   \def\urladdr##1##2{\begingroup
470     \@ifnotempty{##2}{\nobreak\indent
471       \@ifnotempty{##1}{, \ignorespaces##1\unskip}%
472       \url{##2}\par}\endgroup}%
473   \def\orcid##1##2{\begingroup
474     \@ifnotempty{##2}{\nobreak\indent
475       \@ifnotempty{##1}{, \ignorespaces##1\unskip}%
476       ORCID: ##2\par}\endgroup}%
```

```

477 \addresses
478 \endgroup
479 }

```

3.11 Sectioning

```

\contentsnamefont This is the font for the word ‘‘Contents’’:
480 \renewcommand\contentsnamefont{\bfseries}

\section We want our sections to be centered and bold:
481 \def\section{\@startsection{section}{1}%
482 \z@{.7\linespacing\@plus\linespacing}{.5\linespacing}%
483 {\normalfont\bfseries\centering}}

\subsection We want our subsections to be indented and italic:
484 \def\subsection{\@startsection{subsection}{2}%
485 {\parindent}{.5\linespacing}{-.5em}%
486 {\normalfont\itshape}}

\oldsubsections This macro restores the values for \subsection spacing prior to v1.1.
487 \def\oldsubsections{%
488 \gdef\subsection{\@startsection{subsection}{2}%
489 {\parindent}{.5\linespacing\@plus.7\linespacing}{-.5em}%
490 {\normalfont\itshape}}

\subsubsection Subsubsections are formatted exactly like subsections:
491 \def\subsubsection{\@startsection{subsubsection}{3}%
492 {\parindent}{.5\linespacing}{-.5em}%
493 {\normalfont\itshape}}

\Hy@AlphNoErr The newer (circa 2012) hyperref defines this command. However, older versions
do not. Here we provide it:
494 \providecommand\Hy@AlphNoErr[1]{%
495 \ifnum\value{#1}>26 %
496 Alph\number\value{#1}%
497 \else
498 \ifnum\value{#1}<1 %
499 Alph\number\value{#1}%
500 \else
501 \Alph{#1}%
502 \fi
503 \fi
504 }%

\appendix We redefine appendix to ensure the letter in section number is always upright:
505 \def\appendix{\par\c@section\z@ \c@subsection\z@
506 \gdef\theHsection{\Hy@AlphNoErr{section}}%
507 \let\sectionname\appendixname
508 \def\thesection{\upshape\@Alph\c@section}}

```

3.12 Figures and Tables

`\@captionheadfont` This is the font for the words “Figure” or “Table” in captions. Unlike `amsmath` with is small caps, we want just plain Roman font:

```
509 \def\@captionheadfont{\normalfont}
```

3.13 Theorems

Here we redefine three main style of `amsmath`. Here are the arguments of `\newtheoremstyle` from [3]:

```

#1
\newtheoremstyle{NAME}%
#2 #3 #4
{ABOVESPACE}{BELOWSPACE}{BODYFONT}%
#5 #6 #7 #8
{INDENT}{HEADFONT}{HEADPUNCT}{HEADSPACE}%
#9
{CUSTOM-HEAD-SPEC}

```

In the `plain` style the name (“theorem”) is in small caps, the number is in normal font, the optional note is also in normal font, and the text is italics.

```

510 \newtheoremstyle{plain}{0.5\linespacing}{0.5\linespacing}{\sishape}%
511   {\parindent}{\scshape}{.}{0.5em}%
512   {\thmname{#1}\thmnumber{ #2}\thmnote{\normalfont{ } (#3)}}

```

In the `definition` style the name is italics, and the body font is upright:

```

513 \newtheoremstyle{definition}{0.5\linespacing}{0.5\linespacing}%
514   {\upshape}{\parindent}%
515   {\sishape}{.}{0.5em}%
516   {\thmname{#1}\thmnumber{ #2}\thmnote{\normalfont{ } (#3)}}

```

In our class there is no difference between `remark` and `definition` theorem styles:

```

517 \newtheoremstyle{remark}{0.5\linespacing}{0.5\linespacing}%
518   {\upshape}{\parindent}%
519   {\sishape}{.}{0.5em}%
520   {\thmname{#1}\thmnumber{ #2}\thmnote{\normalfont{ } (#3)}}

```

`\newtheorem` For compatibility reasons we need to accept `\newtheorem` with optional first argument—and silently drop it. The problem is, there is `\newtheorem*`, so we need to check which one we deal with... The command `\@xnthm` here is from `amsthm`; it does the real work with the real parameters.

```

521 \renewcommand{\newtheorem}{\@ifstar{\@aom@newthm@star}{\@aom@newthm}}
522 \def\@aom@newthm@star{\@ifnextchar[{\@aom@newthm@star@}{\@aom@newthm@star@[]}}
523 \def\@aom@newthm{\@ifnextchar[{\@aom@newthm@}{\@aom@newthm@[]}}
524 \def\@aom@newthm@star#[1]{\@xnthm *}
525 \def\@aom@newthm#[1]{\@xnthm \relax}

```

```

proof We want our proofs to be indented:
526 \renewenvironment{proof}[1][\proofname]{\par
527 \pushQED{\qed}}%
528 \normalfont \topsep6\p@\@plus6\p@\relax
529 \trivlist
530 \item[\hskip\labelsep\hskip\parindent
531 \itshape
532 #1\@addpunct{.}]\ignorespaces
533 }{%
534 \popQED\endtrivlist\endpfalse
535 }

```

3.14 Bibliography Macros

`\repeatedauthors` When the authors are repeated, we used change them to `\bysame`; we no more do this:

```
536 \def\repeatedauthors#1{\ClassWarning{aomart}{The command is obsolete}#1}
```

`\bysame` We no longer use `\bysame`

```
537 \let\bysame@orig=\bysame
538 \def\bysame{\ClassWarning{aomart}{We no longer omit
539 repeated authors}\bysame@orig}
```

`\doi` Typesetting doi...

```
540 \def\doi#1{%
541 \if@aom@doiMMXVI
542 \url{http://dx.doi.org/#1}%
543 \else
544 \if@aom@olddoi
545 \href{http://dx.doi.org/#1}{doi: \path{#1}}%
546 \else
547 \url{https://doi.org/#1}%
548 \fi
549 \fi}

```

`\mr` Typesetting urls

```

\zbl 550 \def\mr#1{\href{http://www.ams.org/mathscinet-getitem?mr=#1}{MR~\path{#1}}
\arxiv 551 \def\zbl#1{\href{http://www.zentralblatt-math.org/zmath/en/search/?q=an:#1}{Zbl~\path{#1}}}
\jfm 552 \def\arxiv#1{\href{http://www.arxiv.org/abs/#1}{arXiv~\path{#1}}}
553 \def\jfm#1{\href{http://www.emis.de/cgi-bin/JFM-item?#1}{JFM~\path{#1}}}

```

`\bibliofont` We make this `\small` rather than `\Small` in `amsart`

```
554 \renewcommand{\bibliofont}{\small}
```

3.15 Additional Macros

`\EditorialComment` This macro is noop in normal mode, but is a tiny marginpar in the manuscript mode

```

555 \def\EditorialComment#1{\if@aom@manuscript@mode\bgroup
556 \marginparwidth=75pt\marginpar{\scriptsize\raggedright#1}\egroup\fi}

\@fullref This macro creates a wide link for the reference. It has four parameters: the
word (theorem, equation,...), the “pre” punctuation, the reference and the “post”
punctuation.
557 \def\@fullref#1#2#3#4{\hyperref[#3]{#1~#2\ref*{#3}#4}}

\fullref A reference without parentheses:
558 \newcommand{\fullref}[2]{\@fullref{#1}{}{#2}{}}

\pfullref A reference with parentheses:
559 \newcommand{\pfullref}[2]{\@fullref{#1}{(}{#2}{)}}

\bfullref A reference with brackets:
560 \newcommand{\bfullref}[2]{\@fullref{#1}{[}{#2}{]}}

\eqfullref Here we do not use the standard common \@fullref because we want \eqref to
work. . .
561 \newcommand{\eqfullref}[2]{\hyperref[#2]{#1~\textup{\tagform@{\ref*{#2}}}}}

\eqnarray While we do not recommend the use of eqnarray, we still would like to correct
the ugly spacing around it. . .
562 \def\eqnarray{%
563 \stepcounter{equation}%
564 \def\@currentlabel{\p@equation\theequation}%
565 \global\@eqnswtrue
566 \m@th
567 \global\@eqcnt\z@
568 \tabskip\@centering
569 \let\\\@eqnrcr
570 $$\arraycolsep1\p@
571 \everycr{}\halign to\displaywidth\bgroup
572 \hskip\@centering$\displaystyle\tabskip\z@skip{##}$\@eqnse1
573 &\global\@eqcnt\@ne\hskip \tw@\arraycolsep \hfil${##}$\hfil
574 &\global\@eqcnt\tw@ \hskip \tw@\arraycolsep
575 $\displaystyle{##}$\hfil\tabskip\@centering
576 &\global\@eqcnt\thr@@ \hb@xt@\z@\bgroup\hss##\egroup
577 \tabskip\z@skip
578 \cr
579 }

```

3.16 End of Class

```
580 </class>
```

References

- [1] George Grätzer. *Math into L^AT_EX*. Birkhäuser, Boston, third edition, 2000.
- [2] UK T_EX Users Group. UK list of T_EX frequently asked questions. <http://www.tex.ac.uk/cgi-bin/texfaq2html>, 2008.
- [3] Michael Downes and Barbara Beeton. *The amsart, amsproc, and amsbook document classes*. American Mathematical Society, August 2004. <http://mirrors.ctan.org/macros/latex/required/amslatex/classes>.
- [4] Sebastian Rahtz and Heiko Oberdiek. *Hypertext Marks in L^AT_EX: a Manual for Hyperref*, September 2006. <http://mirrors.ctan.org/macros/latex/contrib/hyperref>.
- [5] Heiko Oberdiek. *The ifpdf Package*, February 2006. <http://mirrors.ctan.org/macros/latex/contrib/oberdiek>.
- [6] Piet van Oostrum. *Page Layout in L^AT_EX*, March 2004. <http://mirrors.ctan.org/macros/latex/contrib/fancyhdr>.
- [7] Sergei V. Znamenskii. *Unslanted Punctuation in Computer Modern Italic*, January 2003. <http://mirrors.ctan.org/fonts/cm/cm-tiup>.
- [8] Yannis Haralambous. *My Humble Additions to (La)T_EX Mathematics*, January 1996. <http://mirrors.ctan.org/macros/latex/contrib/yhmath/>.
- [9] American Mathematical Society. *User's Guide for the amsmath Package (Version 2.0)*, February 2002. <http://mirrors.ctan.org/macros/latex/required/amslatex/math/amsl-doc.pdf>.
- [10] Johannes Braams. *Babel, a Multilingual Package For Use With L^AT_EX's Standard Document Classes*, April 2005. <http://mirrors.ctan.org/macros/latex/required/babel>.
- [11] American Mathematical Society. *Instructions for Preparation of Papers and Monographs, AMSL^AT_EX*, August 2004. <http://mirrors.ctan.org/macros/latex/required/amslatex/classes/instr-1.pdf>.
- [12] American Mathematical Society. *Using the amsthm Package*, August 2004. <http://mirrors.ctan.org/macros/latex/required/amslatex/classes/amsthdoc.pdf>.
- [13] Michel Goossens, Sebastian Rahtz, and Frank Mittelbach. *The L^AT_EX Graphics Companion: Illustrating Documents With T_EX and PostScript*. Addison-Wesley Series on Tools and Techniques for Computer Typesetting. Addison-Wesley, Reading, Ma., 1997.

Change History

v0.10		\@setaddresses: Deleted the word URL 25
	\if@aom@screen@mode: Added screen mode 13	E-mail is now in Roman font . 25
	\jfm: Added macro 28	\@setpublishedonline: Decreased font 25
	General: Bibliography styles update 2	\@typesizes: Corrected typo in the definition of Small 14
	Documentation update 2	Increased LARGE from 16 pt to 17 pt 14
	Screen mode triggers special URL settings 13	\bfullref: Added macro 29
v0.2		\emailaddrname: Changed macro 25
	General: First fully functional version 2	\eqfullref: Added macro 29
v0.3		\fullref: Added macro 29
	\EditorialComment: Added macro 28	\pfullref: Added macro 29
	\arxiv: Added macro 28	\subsection: Redefined macro . . 26
	\corresponding: Added macro . . 21	General: Added extra footer in manuscript mode 16
	\doinumber: Added macro 21	Corrected the byg with math in headers 16
	\if@aom@manuscript@mode: Added manuscript mode 12	Made remark theorem style identical to definition theorem style 27
	\mr: Added macro 28	Made Roman font the default URL font 13
	\mrnumber: Added macro 21	proof: Redefined macro 28
	\newtheorem: Redefined macro . . 27	v0.6
	\proposed: Added macro 21	\@setauthors: 'By' and 'and' are in Roman font now 23
	\seconded: Added macro 21	\belowdisplayskip: Changed belowdisplayskip 15
	\version: Added macro 21	\bibliofont: Changed default . . 28
	\zbl: Added macro 28	\zbl: Changed capitalization . . . 28
	\zblnumber: Added macro 21	General: Changes to bst files 2
	General: Added DOI number in headers 16	Fullref.pl is much less aggressive now 2
	Added package mdputu 14	v0.7
	Documentation update 2	General: Bibliography styles changed 2
v0.4		v0.8
	\@aom@linecount: Added macro . 16	\specialdigits: Redefined to noop 14
	\enddoc@text: Deleted many dates. 25	General: Added yhmath 14
	General: Changed definition theorem style 27	Bibliography styles update 2
	Changed plain theorem style . 27	Changed authors in header . . . 16
	Deleted lineno package dependence 14	Documentation update 2
	Deleted remark theorem style . 27	Switched to cmtiup 14
	Documentation update 2	
	Switched to upright digits in italics everywhere 14	
	Used line numbers for headings 16	
v0.5		
	\@fullref: Added macro 29	

v0.9		Deleted \repeatedauthors from the documentation	2
	\@@and: Redefined macro		24
	\@setaddresses: Deleted spurious space in urladdress		25
	\@setpublishedonline: Increased font		25
	\eqnarray: Redefined standard macro		29
	General: Bibliography styles update		2
	Changed font for the folio on the first page		16
	Documentation update		2
	abstract: Added parindent for the first par		21
v1.0			
	\doinumber: Added default		21
	\papernumber: Added macro		20
	General: Top matter macros are now only in preamble		2
v1.1			
	General: In manuscript mode the links are always blue		13
v1.10			
	\@@and: Added internationalization		24
	\@aom@and: Added macro		14
	\@aom@by: Added macro		14
	\@setauthors:		
	Internationalization		23
	\doi: Introduced the logic for old doi formatting		28
	\if@aom@olddoi: Added old DOI processing		13
v1.11			
	\@adminfootnotes: Added copyright statement		23
	\@setaddresses: Changed email handling		25
	\bysame: Made the macro obsolete		28
	\copyrightnote: Added macro		21
	\copyrightyear: Added macro		21
	\fulladdress: Added macro		18
	\repeatedauthors: Now this command is obsolete		28
	General: Added \fulladdress		2
	Added new commands for copyright statement		2
	Bibliography change: titlenote, deleted bysame		2
		Deleted \repeatedauthors from the documentation	2
		v1.12	
		\appendix: Added hyperref definition	26
		v1.13	
		\Hy@AlphNoErr: Added macro for older installations	26
		v1.14	
		\@mainrpi: Added macro	21
		\@maketitle@hook: Added macro	22
		\aom@write@paper@info: Added macro	21
		v1.14a	
		\annalsurl: New url	17
		v1.15	
		\doi: Doi according to the new Crossref recommendations	28
		\if@aom@doiMMXVI: Added another options	13
		v1.16	
		\aom@write@paper@info: Added names, abstract, subjects, keywords, zblnumber, arxivnumber	21
		Corrected the endpage bug	21
		\arxivnumber: Added macro	21
		\author: Redefined amsart definition	18
		\email: Redefined amsart definition	18
		\fulladdress: Redefined	18
		\givenname: Redefined	18
		\surname: Redefined	18
		\urladdr: Redefined amsart definition	18
		General: We require environ package	14
		abstract: Redefined using environ	21
		v1.17	
		General: Added new field totalpages to the bibliography	2
		v1.17a	
		General: Bug fixed in aomplain.bst	2
		v1.18	
		\@setaddresses: Added orcid	25
		\@setkeywords: Now we print keywords	24
		\@setsubjects: Now we print subjects	24

<code>\ifaomoldkeywords</code> : Added keywords processing	13	<code>\setsubjects</code> : Make primary and secondary subjects separated .	24
<code>\orcid</code> : Added macro	18	<code>\aomwritepaperinfo</code> : Make primary and secondary subjects separated	21
<code>\subject</code> : Drop scheme and primary/secondary	19	<code>\subject</code> : Make primary and secondary subjects separated .	19
General: New option <code>oldkeywords</code> and printing keywords and subjects by default	2	v1.3	
v1.19		General: Corrected bug with <code>doinumber</code>	16
General: Bibliography changes . . .	2	v1.4	
v1.2		<code>\subsection</code> : Deleted stretch in vertical spacing	26
<code>@setaddresses</code> : Changed font for current address	25	<code>\subsubsection</code> : Introduced the macro	26
<code>\arxiv</code> : Now we properly treat numbers with underscores . . .	28	General: Deleted <code>noamfonts</code> option	13
<code>\doi</code> : Now we properly treat numbers with underscores . . .	28	v1.5	
<code>\jfm</code> : Now we properly treat numbers with underscores . . .	28	<code>\arxiv</code> : Typo corrected	28
<code>\mr</code> : Now we properly treat numbers with underscores . . .	28	General: Added <code>noopsort</code> to the styles, corrected typo	2
<code>\oldsubsections</code> : Introduced macro	26	Added <code>sortyear</code> to the styles . . .	2
<code>\subsection</code> : Decreased vertical spacing	26	v1.6	
<code>\zbl</code> : Now we properly treat numbers with underscores . . .	28	<code>\appendix</code> : Redefined the macro .	26
General: Bibliography styles update	2	General: Bibliography change: <code>aomalpha</code> now respects key field in the bib file	2
v1.20		v1.7	
<code>@adminfootnotes</code> : Make primary and secondary subjects separated	23	General: Suppressed page number in the header for one-page articles	16
		v1.9	
		<code>\doi</code> : Changed doi look	28

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
<code>\@and</code>	377, <u>439</u>	
<code>\@Alpha</code>	508	
<code>\@M</code>	456	
<code>\@accepted</code>	246, 247, 447	
<code>\@addpunct</code> . . .	409, 532	
<code>\@adminfootnotes</code> . .	<u>396</u>	
<code>\@annalsurl</code> . . .	138, 153	
<code>\@aom@abstract</code>	267, 269, 355	
<code>\@aom@and</code>	<u>70</u> , 72–74, 377, 439	
<code>\@aom@by</code> . . .	<u>69</u> , 72–74, 383	
<code>\@aom@doiMMXVIfalse</code>	42	
<code>\@aom@doiMMXVItrue</code> .	43	
<code>\@aom@linecount</code> . . .	108, 122, 125, 134	
<code>\@aom@manuscript@modefalse</code>	33	
<code>\@aom@manuscript@modetrue</code>	34	
<code>\@aom@newthm</code> . . .	521, 523	
<code>\@aom@newthm@</code> . . .	523, 525	
<code>\@aom@newthm@star</code>	521, 522	
<code>\@aom@newthm@star@</code>	522, 524	
<code>\@aom@olddoifalse</code> . .	39	
<code>\@aom@olddoittrue</code> . .	40	
<code>\@aom@oldkeywordsfalse</code>	45	
<code>\@aom@oldkeywordstrue</code>	46	
<code>\@aom@screen@modefalse</code>	36	
<code>\@aom@screen@modetrue</code>	37	
<code>\@arxivnumber</code>	297, 345, 347	
<code>\@captionheadfont</code> . .	<u>509</u>	
<code>\@centering</code>	568, 572, 575	
<code>\@closetoccontribs</code> .	387	
<code>\@copyrightnote</code>	301, 408, 409	319, 321, 323, 325, 327, 329,
<code>\@copyrightyear</code>	299, 303	331, 333, 335,
<code>\@currentlabel</code>	564	338, 342, 346,
<code>\@date</code>	398	349, 352, 354, 356
<code>\@dblarg</code>	211	<code>\@makefnmark</code>
<code>\@doinumber</code>	149–151, 291, 336	397
<code>\@empty</code>	149, 195,	<code>\@maketitle@hook</code> . .
	204, 225, 227,	<u>359</u>
	228, 230, 243,	<code>\@mrnumber</code> 293, 341, 343
	245, 247, 249,	<code>\@names</code>
	251, 263, 303,	193, 197, 200,
	337, 341, 345,	215, 219, 223, 320
	359, 370, 384,	<code>\@ne</code>
	398–402, 405,	111, 113, 573
	408, 421, 422,	<code>\@nx</code>
	425, 426, 441–444	211, 212
<code>\@endformatdate</code>	235, 236	<code>\@onlypreamble</code> 155–189
<code>\@endpfalse</code>	534	<code>\@par</code>
<code>\@eqcnt</code> 567, 573, 574, 576		406, 409
<code>\@eqncr</code>	569	<code>\@percentchar</code>
<code>\@eqnsel</code>	572	318, 320, 322,
<code>\@eqnswtrue</code>	565	324, 326, 328,
<code>\@footnotetext</code>	398, 399,	330, 332, 334,
	405, 408, 417, 436	336, 339, 343,
<code>\@formatdate</code>	235, <u>236</u>	347, 350, 353, 355
<code>\@fullref</code>	<u>557</u> , 558–560	<code>\@plus</code> 280, 482, 489, 528
<code>\@getabstract</code>	<u>267</u> , 285	<code>\@primarysubjects</code>
<code>\@gobble</code>	287–290	227, 350,
<code>\@ifnextchar</code>	522, 523	401, 422, 423, 426
<code>\@ifnotempty</code>	203, 459, 462,	<code>\@published</code> 248, 249, 448
	463, 466, 467,	<code>\@publishedonline</code>
	470, 471, 474, 475	250, 251, 449
<code>\@ifpackageloaded</code> . .	71	<code>\@received</code>
<code>\@ifstar</code>	521	242, 243, 442, 445
<code>\@ixpt</code>	84	<code>\@revised</code>
<code>\@keywords</code> 225, 226,		244, 245, 443, 446
353, 400, 414, 417		<code>\@secondarysubjects</code>
<code>\@mainrpi</code>	<u>305</u> , 309, 317,
		228, 351,
		402, 425, 427, 429
		<code>\@setabstract</code>
		286
		<code>\@setabstracta</code>
		286
		<code>\@setaccepted</code>
		<u>445</u>
		<code>\@setaddresses</code> 444, <u>451</u>
		<code>\@setauthors</code>
		<u>369</u>
		<code>\@setcontribs</code> . 386, <u>392</u>
		<code>\@setdate</code>
		398
		<code>\@setkeywords</code> . 400, <u>412</u>

\@setpublished	<u>445</u>	\abstractbox	274	\c@section	505, 508
\@setpublishedonline		\abstractname	276	\c@subsection	505
.	<u>445</u>	\accepted	7, 170, <u>242</u>	\captionenglish	74
\@setreceived	442, <u>445</u>	\address	5, 158, 457	\captionfrench	72
\@setrevised	443, <u>445</u>	\addresses	201, 214, 218, 222, 444, 477	\captionsgerman	73
\@setsubjclass	399	\addto	72–74	\centering	276, 374, 445–449, 483
\@setsubjects		\advspace	454, 458	\cfoot	152
.	403, 404, <u>420</u>	\advance	113, 375	\chead	137
\@setthanks	406	\Alph	501	\ClassInfo	49, 51
\@settitle	<u>360</u>	\and	199, 200, 207, 310	\ClassWarning	25, 78, 271, 536, 538
\@settranslators	441	\annalsurl	<u>153</u>	\closeout	356
\@startsection		\aom@size@warning	24, 27–31	\clubpenalty	<u>103</u>
.	481, 484, 488, 491	\aom@write@paper@info	<u>306</u> , 359	\Collect@Body	285
\@subjclass	399	\appendix	<u>505</u>	\contentsnamefont	<u>480</u>
\@subjects	421, 423, 427, 429, 433, 436	\appendixname	507	\contribs	384
\@tempa	262, 263, 312, 315, 334	\arraycolsep	570, 573, 574	\copyrightnote	6, 181, <u>301</u>
\@tempc	314, 315	\arxiv	<u>11</u> , <u>550</u>	\copyrightyear	7, <u>299</u>
\@tempcnta		\arxivnumber	7, 189, <u>291</u>	\copyrighyear	182
.	111–113, 237, 241	\AtBeginDocument	71	\corresponding	7, 175, <u>289</u>
\@thefnmark	397	\author	5, 156, <u>194</u> , 454	\cr	578
\@title	322, 363, 365	\author@andify	378	\csname	212, 230, 231, 233
\@topsep	374, 375	\authors	195, 196, 199, 318, 370, 378, 380, 383	\curraddr	5, 159, 461
\@translators	441			\curraddrname	462
\@typesizes	<u>83</u>	B		\currentissue	253, 292, 328
\@undefined	311	\baselineskip	89, 361, 375	\CurrentOption	27–31, 47
\@viipt	84	\begin	19, 121, 124, 133, 360	\currentpaper	255, 292, 330
\@viipt	84	\beginingroup	371, 452, 457, 461, 465, 469, 473	\currentvolume	138, 252, 292, 326
\@vipt	84			\currentyear	139, 254, 292, 303, 324
\@xcontribs	393	\belowdisplayskip	<u>95</u>	D	
\@xiipt	87	\bfseries	276, 362, 480, 483	\DeclareOption	27–31, 34, 37, 40, 43, 46, 47
\@xipt	86	\bfullref	9, <u>560</u>	\def	24, 69, 70, 72–74, 80, 83, 141, 153, 190–193, 225, 229, 235, 236, 242, 244, 246, 248, 250, 252– 255, 257, 258, 260, 262–265,
\@xnthm	524, 525	\bgroup	274, 307, 555, 571, 576		
\@xp	212	\bibliofont	<u>554</u>		
\@xpt	85	\bigskipamount	454, 458		
\@xvipt	87	\bysame	<u>537</u>		
\@zblnumber	295, 337, 339	\bysame@@orig	537, 539		
\\	112, 148, 382, 455, 569	C			
10pt (option)	5	\c@page	259		
11pt (option)	5				
12pt (option)	5				
8pt (option)	5				
9pt (option)	5				
A					
\abovedisplayskip	<u>95</u>				
\abstract	<u>285</u>				
abstract (environ- ment)	6				

267, 268, 291,	<code>\end@page</code> 143,	<code>\footnotesize</code> . 119,
293, 295, 297,	146, 148, 263, 264	121, 152, 374, 453
299, 301, 306,	<code>\endcsname</code>	<code>\footrulewidth</code> <u>106</u>
310, 314, 359,	. 212, 230, 231, 233	<code>\footskip</code> <u>100</u>
360, 369, 372,	<code>\enddoc@text</code> <u>440</u>	<code>\formatdate</code> 7, <u>235</u>
377, 382, 392,	<code>\endgroup</code>	<code>\fulladdress</code> 5, 163, <u>190</u>
396, 406, 409,	. 390, 460, 464,	<code>\fullref</code> 9, <u>558</u>
412, 420, 439,	468, 472, 476, 478	<code>\fullwidthdisplay</code> . 281
440, 445–451,	<code>\endlist</code> 284	
454, 455, 457,	<code>\endpage</code> 7, 185, <u>262</u> , 265	G
461, 465, 469,	<code>\endtrivlist</code> .. 389, 534	<code>\g@addto@macro</code> 191–
473, 481, 484,	environments:	193, 197, 199–
487, 491, 505,	<code>abstract</code> 6	201, 207, 214,
508, 509, 522–	<code>eqnarray</code> 8	215, 218, 219,
525, 536, 538,	<code>eqnarray*</code> 8	222, 223, 226, 233
540, 550–553,	<code>\eqfullref</code> 9, <u>561</u>	<code>\gdef</code> 153, 196,
555, 557, 562, 564	<code>\eqnarray</code> <u>562</u>	205, 225, 231,
<code>\dimen</code> 99	<code>eqnarray</code> (environ-	269, 291, 293,
<code>\displaystyle</code> . 572, 575	ment) 8	295, 297, 488, 506
<code>\displaywidth</code> 571	<code>eqnarray*</code> (environ-	<code>\givenname</code> . 5, 162, <u>190</u>
<code>\DocInput</code> 20	ment) 8	<code>\global</code> 274, 359, 565,
<code>\documentclass</code> 8	<code>\evensidemargin</code> <u>93</u>	567, 573, 574, 576
<code>\doi</code> 11, 151, <u>540</u>	<code>\everycr</code> 571	H
<code>doi2016</code> (option) 4	<code>\expandafter</code> .. 151,	<code>\halign</code> 571
<code>\doinumber</code> . 7, 186, <u>291</u>	230, 231, 233, 315	<code>\hb@xt@</code> 576
<code>draft</code> (option) 4		<code>\headrulewidth</code> <u>106</u>
E	F	<code>\headsep</code> <u>105</u>
<code>\edef</code> . 142, 144, 146,	<code>\fancyfoot</code> . . . 117, 127	<code>\hfil</code> 573, 575
150, 211, 312,	<code>\fancyhead</code> 116, 118,	<code>\href</code> 138,
315, 423, 427, 429	119, 121, 124, 129	468, 545, 550–553
<code>\editor</code> 7, 176	<code>\fancyhf</code> 131	<code>\hskip</code> 463,
<code>\EditorialComment</code> 8, <u>555</u>	<code>\fancypagestyle</code> . . . 130	467, 530, 572–574
<code>\egroup</code> 284, 358, 556, 576	<code>\fi</code> . . . 66, 114, 128,	<code>\hss</code> 576
<code>\else</code> 60, 63,	136, 147, 148,	<code>\Hy@AlphNoErr</code> . <u>494</u> , 506
145, 148, 149,	151, 202, 208,	<code>\hyperref</code> 557, 561
198, 206, 225,	226, 234, 240,	<code>\hypersetup</code> 58, 61, 64,
232, 264, 303,	261, 264, 273,	365, 380, 414, 433
313, 337, 341,	286, 303, 316,	<code>\HyPsd@0@pageref</code> .. 144
345, 370, 385,	340, 344, 348,	
398–400, 403–	357, 366, 381,	I
405, 408, 416,	388, 391, 398–	<code>\if@aom@doiMMXVI</code> <u>41</u> , 541
422, 425, 428,	400, 403, 404,	<code>\if@aom@manuscript@mode</code>
435, 441–444,	407, 410, 415, <u>32</u> , 60,
497, 500, 543, 546	418, 424, 430,	108, 120, 132, 555
<code>\email</code> .. 5, 157, <u>213</u> , 465	431, 434, 437,	<code>\if@aom@olddoi</code> . <u>38</u> , 544
<code>\emailaddrname</code> <u>450</u> , 466	441–444, 502,	<code>\if@aom@oldkeywords</code>
<code>\EnableCrossrefs</code> .. 18	503, 548, 549, 556 <u>44</u> , 416, 435
<code>\end</code> 21, 123, 126, 135, 367	<code>final</code> (option) 4	<code>\if@aom@screen@mode</code>
	<code>\footins</code> <u>95</u> <u>35</u> , 57

<code>\if@filesw</code>	308	<code>\list</code>	277	<code>doi2016</code>	4
<code>\ifcase</code>	238	<code>\listparindent</code>	279	<code>draft</code>	4
<code>\IfFileExists</code>	76	<code>\LoadClass</code>	54	<code>final</code>	4
<code>\ifnum</code> 113, 259, 495, 498		<code>\long</code>	24, 267–269	<code>manuscript</code>	4
<code>\ifpdf</code> 364, 379, 413, 432		<code>\loop</code>	112	<code>olddoi</code>	4
<code>\ifx</code>	143, 148, 149, 195, 204, 225, 230, 263, 270, 286, 303, 311, 337, 341, 345, 370, 384, 398–402, 405, 408, 422, 425, 426, 441–444	M		<code>oldkeywords</code>	4
<code>\ignorespaces</code>	455, 459, 460, 463, 467, 471, 475, 532	<code>\m@th</code>	566	<code>screen</code>	4
<code>\indent</code>	458, 462, 466, 470, 474	<code>\MakeLowercase</code>	439	<code>\or</code>	84–88, 238–240
<code>\InputIfFileExists</code>	48	<code>\maketitle</code>	6, 270, 272	<code>\orcid</code>	5
<code>\interlinepenalty</code>	456	<code>\MakeUppercase</code>	129	<code>\overline</code>	10, 90
<code>\issuenum</code> 7, 179, <u>253</u>		<code>manuscript (option)</code>	4	P	
<code>\item</code>	283, 376, 530	<code>\marginpar</code>	556	<code>\p@</code> 280, 361, 374, 528, 570	
<code>\itemindent</code>	279	<code>\marginparwidth</code>	556	<code>\p@equation</code>	564
<code>\itshape</code>	81, 450, 486, 490, 493, 531	<code>\MessageBreak</code>	78	<code>\PageIndex</code>	15
J		<code>\mr</code>	11, <u>550</u>	<code>\pagenumbering</code> 257, 259	
<code>\jfm</code>	11, <u>550</u>	<code>\mrnumber</code>	7, 187, <u>291</u>	<code>\pageref</code>	141, 263
<code>\jobname</code>	309	N		<code>\pagespan</code>	<u>265</u>
K		<code>\NeedsTeXFormat</code>	1	<code>\pagestyle</code>	115
<code>\keyword</code>	6, 166, <u>225</u>	<code>\newcommand</code> 221, 558–561		<code>\papernumber</code> 7, 183, <u>255</u>	
L		<code>\newif</code>	32, 35, 38, 41, 44	<code>\par</code>	276, 406, 409, 445– 449, 451, 458, 460, 464, 468, 472, 476, 505, 526
<code>\labelsep</code>	530	<code>\newsavebox</code>	109	<code>\parbox</code>	110
<code>\labelwidth</code>	277	<code>\newtheorem</code>	9, <u>521</u>	<code>\parindent</code>	<u>101</u> , 485, 489, 492, 511, 514, 518, 530
<code>\LARGE</code>	362	<code>\newtheoremstyle</code>	510, 513, 517	<code>\parsep</code>	280
<code>\leftmargin</code>	278	<code>\newwrite</code>	305	<code>\parskip</code>	<u>101</u>
<code>\let</code>	10, 81, 82, 90, 227, 228, 243, 245, 247, 249, 251, 281, 287–290, 359, 397, 406, 409, 421, 507, 537, 569	<code>\nobreak</code>	452, 454, 462, 466, 470, 474	<code>\PassOptionsToClass</code> 47	
<code>\thead</code>	133	<code>\nolinkurl</code>	468	<code>\path</code>	545, 550–553
<code>\linebreak</code>	382	<code>\normalfont</code>	276, 283, 483, 486, 490, 493, 509, 512, 516, 520, 528	<code>\penalty</code>	386
<code>\linespacing</code>	89, 482, 485, 489, 492, 510, 513, 517	<code>\normalparindent</code>	279	<code>\pfullref</code>	9, <u>559</u>
		<code>\normalsize</code>	89, 276	<code>\popQED</code>	534
		<code>\number</code>	496, 499	<code>\ProcessOptions</code>	53
		O		<code>\proof</code>	<u>526</u>
		<code>\oddsidemargin</code>	<u>93</u>	<code>\proofname</code>	526
		<code>olddoi (option)</code>	4	<code>\proposed</code>	7, 173, <u>287</u>
		<code>oldkeywords (option)</code>	4	<code>\protect</code>	272, 372, 382
		<code>\oldsubsections</code>	8, <u>487</u>	<code>\protected@write</code>	317, 319, 321, 323, 325, 327, 329, 331, 333, 335, 338, 342, 346, 349, 352, 354
		<code>\openout</code>	309	<code>\providecommand</code>	494
		options:		<code>\ProvidesClass</code>	5
		10pt	5		
		11pt	5		
		12pt	5		
		8pt	5		
		9pt	5		

<code>\ProvidesFile</code>	3	<code>\setcounter</code>	257, 259	<code>\thmname</code>	512, 516, 520
<code>\publicationyear</code>	7, 180, <u>254</u>	<code>\setlength</code>	91, 92, 95–102, 105	<code>\thmnote</code>	512, 516, 520
<code>\published</code>	7, 171, <u>242</u>	<code>\shortauthors</code>	6, 129, 204, 205, 207	<code>\thmnumber</code>	512, 516, 520
<code>\publishedonline</code>	7, 172, <u>242</u>	<code>\shorttitle</code>	118	<code>\thr@@</code>	576
<code>\pushQED</code>	527	<code>\sishape</code>	81, 510, 515, 519	<code>\title</code>	5, 155
<code>\put</code>	122, 125, 134	<code>\skip</code>	98	<code>\topsep</code>	528
Q					
<code>\qed</code>	527	<code>\Small</code>	283	<code>\topskip</code>	<u>95</u>
R					
<code>\r@LastPage</code>	311, 315	<code>\small</code>	383, 554	<code>\trivlist</code>	373, 529
<code>\raggedright</code>	556	<code>\space</code>	241, 272, 310, 386, 463, 467	<code>\tw@</code>	573, 574
<code>\received</code>	7, 168, <u>242</u>	<code>\specialdigits</code>	<u>80</u>	U	
<code>\RecordChanges</code>	17	<code>\start@page</code>	140, 142, 258, 260, 312, 332	<code>\underline</code>	112
<code>\ref</code>	557, 561	<code>\startpage</code>	7, 184, <u>257</u> , 265	<code>\unskip</code>	455, 459, 463, 467, 471, 475
<code>\relax</code>	53, 111, 230, 237, 270, 281, 286, 361, 370, 374, 376, 397, 525, 528	<code>\stepcounter</code>	563	<code>\upshape</code>	377, 508, 514, 518
<code>\renewcommand</code>	106, 107, 194, 213, 217, 480, 521, 554	<code>\string</code>	212, 310	<code>\url</code>	472, 542, 547
<code>\renewenvironment</code>	285, 526	<code>\subject</code>	6, 167, <u>227</u>	<code>\urladdr</code>	5, 160, <u>217</u> , 469
<code>\repeat</code>	113	<code>\subsection</code>	<u>484</u> , 488	<code>\urlstyle</code>	67
<code>\repeatedauthors</code>	<u>536</u>	<code>\subsubsection</code>	<u>491</u>	<code>\usebox</code>	122, 125, 134
<code>\RequirePackage</code>	55, 56, 68, 75, 77	<code>\surname</code>	5, 164, <u>190</u>	<code>\usepackage</code>	9, 11–13
<code>\revised</code>	7, 169, <u>242</u>	T			
<code>\rightmargin</code>	278	<code>\tabskip</code>	568, 572, 575, 577	<code>\value</code>	495, 496, 498, 499
<code>\romannumeral</code>	260	<code>\tagform@</code>	561	<code>\version</code>	7, 177, <u>290</u>
S					
<code>\savebox</code>	110	<code>\tempa</code>	141, 143, 144, 146, 148	<code>\vglue</code>	275, 276
<code>screen</code> (option)	4	<code>\tempb</code>	142, 148	<code>\volumenumber</code>	7, 178, <u>252</u>
<code>\scriptsize</code>	112, 118, 127, 129, 137, 556	<code>\textbf</code>	138	<code>\vtop</code>	274
<code>\scshape</code>	383, 394, 460, 463, 464, 511	<code>\textcopyright</code>	302	W	
<code>\seconded</code>	7, 174, <u>288</u>	<code>\textheight</code>	<u>91</u>	<code>\widebar</code>	8, 10, <u>90</u>
<code>\section</code>	<u>481</u>	<code>\textit</code>	82	<code>\widehat</code>	8
<code>\sectionname</code>	507	<code>\textsi</code>	82	<code>\wideparen</code>	8
<code>\setbox</code>	274	<code>\textsup</code>	561	<code>\widering</code>	8
		<code>\textwidth</code>	<u>91</u>	<code>\widetilde</code>	8
		<code>\thanks</code>	6, 165, 372	<code>\widetriangle</code>	8
		<code>\thanks@warning</code>	372	<code>\widowpenalty</code>	<u>103</u>
		<code>\thankses</code>	405	X	
		<code>\the</code>	112, 241	<code>\xcontributes</code>	394
		<code>\theequation</code>	564	Z	
		<code>\theHsection</code>	506	<code>\z@</code>	102, 259, 277, 280, 482, 505, 567, 576
		<code>\thepage</code>	119, 121, 152	<code>\z@skip</code>	572, 577
		<code>\thesection</code>	508	<code>\zbl</code>	11, <u>550</u>
				<code>\zblnumber</code>	7, 188, <u>291</u>